

SOLO - W

Smart Trail Camera/Camera Trap

SOLO-W operates solely in critical areas without GSM coverage, waking up upon presence detection to record electro-optic and thermal videos. It performs on-device analysis using edge AI and sends detection photos of humans, vehicles, etc., to HUB via Wi-Fi, making it ideal for surveillance in areas like critical trespassing trails where conventional networks are unavailable.

The integration of edge AI is vital, as it filters data on the device, ensuring only relevant detection events are transmitted. Wi-Fi is only activated when transmitting images from SOLO-W to HUB. This efficiency enhances privacy, reduces the volume of data sent, decreases latency, and lowers communication costs by avoiding false positives.

SOLO-W's design includes camouflage capabilities, allowing it to blend into its surroundings and avoid detection.

With its motion detection feature, SOLO-W automatically records and analyzes footage, enabling real-time response to potential threats. This makes SOLO-W a dependable and efficient surveillance system for secure, autonomous operation in remote and sensitive locations.



TECHNICAL SPECIFICATIONS

PARAMETERS	SPECIFICATIONS	PARAMETERS	SPECIFICATIONS
Mass ¹	1.2 kg	Wake-up Method	3 x Motion Sensor
Dimension	104x128x108 mm	Wake-up Range	30 m
Power Source	12V Battery (External)	Image Sensor	Electro-Optical and Thermal Camera
Operation Time ²	180 days	Illumination	Infrared (IR) LED (Invisible)
Operating Temperature	-20 to +50 °C	Image Analysis	Detection on the Edge Device with AI (Person, Animal, Vehicle, Other)
Ingress Protection Class	IP68	Data Encryption	AES-256
Data Transmission ³	Wi-Fi	User Interfaces ⁵	Web and Mobile Applications
Coverage ⁴	World-wide		

CARRYING CASE

Mass	1.72 kg (empty)	Dimensions	345x302x150 mm
Ingress Protection Class	IP67	Other	MIL-STD-810G

¹ May vary depending on configuration. ² Operation time depends on battery capacity and number. ³ HUB is required for SOLO-W to operate. ⁴ Coverage area varies according to the preferred satellite network. ⁵ Mobile devices with Android and IOS operating system are supported.

SOLO – W

Smart Trail Camera/Camera Trap

ADDITIONAL REQUIREMENTS

POWER SOURCE

12V external power supply (battery) is required and not included in the box. 12V 24 Ah battery is suggested for up to 2 months of use.

MANAGEMENT and ANALYSIS SYSTEM

For effective data gathering and analysis, each SOLO-W unit must be connected to the CENTRAL (Management and Analysis System) or integrated with the customer's services via API. We provide a complimentary service that relays data to the specified software/service endpoints or email addresses of the customer using API integration. Users must select one of the following options for CENTRAL usage:

- **Cloud Use:** Offers unlimited device management at an annual fee per device within the Cloud Panel.
- **On-Prem Use:** With annual payment, CENTRAL can support an unlimited number of devices.

WARRANTY COVERAGE

The product comes with a limited 2-year warranty.

BOX CONTENT

Each SOLO-W set comes in a carrying case containing:

- SOLO-W Device (1 Unit)
- Antenna (2 Unit)
 - Wi-Fi (1 Unit)
 - LoRa (1 Unit)
- Connection Strap (2 Units)
- Power and Data Cable (1 Unit)
- Battery Cable (1 Unit)
- SOLO-W Ethernet Module (1 Unit)
- User Manual (1 Unit)